



The RC5-UNI™ supports multiple camera models:


- Angekis Saber Plus
- AVer PTC500+
- AVer TR530
- AVer TR530
- Lumens VC-A50P/PN
- Lumens VC-A61P
- Lumens VC-A71P
- Lumens VC-TA50
- Marshall CV630
- Marshall CV730
- Minrray UV401A
- Minrray UV 540-05/10-HDMI
- PTZ Optics PT12X-SDI
- PTZ Optics PT20X-SDI
- PTZ Optics PT30X-SDI
- QSC Q-SYS PTZ 12x72
- QSC Q-SYS PTZ 20x60
- Sony SRG-120DH
- Sony SRG-300H
- Sony SRG-360SHE
- Sony SRG-X120
- Sony SRG-X40UH
- Sony SRG-X400
- Sony BRC-X400
- VDO360 Saber20X NDI

Shown: Sony SRG-X120



### SCTLink™ Cable Specs

Integrator-Supplied CAT5e/CAT6 STP/UTP Cable  
T568A or T568B (10m-100m min/max Length)



RCC-H001-1.0M  
HDMI to HDMI Video Cable



RCC-C001-0.3M  
HDMI to HDMI Video Cable

RCC-C002-0.3M  
RJ45 to RJ45 UTP Control Cable

PPC-004-0.4M  
Power Cable

SCTLink™ Cable  
Power, Control & Video  
The SCTLink™ cable must always be a single, point-to-point CAT cable with no couplers or interconnections.

RCC-H016-1.0M  
RJ45 to RJ45  
UTP Control Cable

Sony RM-IP10 Joystick  
or Generic Controller

WPS-12 30VDC  
100-240V 47-63Hz  
Power Supply

Sony 120V  
Power Supply

### Module Dimensions

RC5-CE™: H: 0.93" (23mm) x W: 2.5" (63mm) x D: 3.741" (95mm)

RC5-HE™: H: 1.504" (38mm) x W: 3.813" (96mm) x D: 3.617" (91mm)

