

SRG Box/PoV Series



NEW Compact size that fits easily into any environment with upper and lower tripod mount for installation flexibility. Large, easy-to-see tally lamp suitable for multiple camera applications and robustness guaranteed thanks to rear panel guards.



Specifications	SRG-XP1	SRG-XB25
Interface	HDMI 2.0 / Ethernet / USB3.0	HDMI 2.0 / Ethernet
Sensor	1/1.8" 8.42MP CMOS	1/2.5" 8.5MP CMOS
Signal format	3840p / 1080p / 1080i / 720p / 480p (480p is only for HDMI) & UVC MJPEG	
Frame Rate	59.94/50/29.97/25	
IP Video Streaming	RTSP / RTMP(S) / SRT / MPEG-TS and NDI® HX (optional)	
Optical Zoom	No	25X
Digital Zoom	6x (including pixel zoom)	
Pan / Tilt / Zoom	ePTZ	No
Horizontal Viewing Angle	102°	68°
Audio Output	No	Yes
Audio Input	3.5mm x1	
Power	12VDC +/-20%	
POE	Yes (IEEE802.3af)	
Control	VISCA over IP / ONVIF Profile S / CGI command / UVC	VISCA over IP / ONVIF Profile S / VISCA / CGI command
Ceiling Mount	Yes. Tripod Mount (upper & lower)	

For full product specifications and features please visit pro.sony/network-camera-systems